

# SMARTFACE 603S

Model:DM603S



The DOUBLE-SIDED designed SMARTFACE 603S is an ultra compact and light weight stylish moving head WASH+STROBE light (2 Faces). Face 1 features 60\*3W 3-IN-1 RGB LEDs which is designed with 6 individual segments. It's available for 2800K-5600K color temperature adjustment. Face 2 features 324\*0.5W 5730 WW+CW LEDs which is designed with 9 individual rings. It's available for 2500K-4600K color temperature adjustment. The fixture could be used not just only as a wash light (specially moving face light) but also as a remarkable moving strobe light.

It provides 360° continuous fast and smooth PAN/TILT movement with variable speed which delivers even more vivid visual effect to the show. The fixture supports DMX, RDM (Remote Device Management).

It features excellent color mixing, quiet running and flicker free control. The fixture is built in with different internal dynamic effect with variable speed. The moving head also features optimum optic design integrated with extremely effective aluminum heat sink system.

The fixture's exterior housing is beautifully balanced basing on a modern design philosophy with supremely harmonious interior structure for remarkable control. The sculpted body of the SMARTFACE 603S achieves more than just a striking look. The 2\*1/4 turn fastening omega clamps, available for vertical and horizontal plug-in, make installations fast and easy.

The SMARTFACE 603S is designed for applications as concerts, TV studios, banquet halls, bars, pubs, DJ entertainment, ballrooms, etc.

## Light Source

Source:  
Face 1:  
60\*3W 3-IN-1 LEDs (RGB)  
6 Individual control segments  
Face 2:  
324\*0.5W 5730 LEDs (WW+CW )  
9 Individual control rings  
Flicker free operation for broadcast TV and FILM  
Life Span: 50000H  
The life span may vary depending on several following factors but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming)

## Optics

Face 1:  
High efficiency optic system  
25°Beam angle (other angles optional)  
35°Field angle  
Face 2:  
120°Field angle  
High output

## Movement

PAN: 2 modes  
1. 360°Continuous movement  
2. 540°(8/16 bit)  
TILT: 2 modes  
1. 360°Continuous movement  
2. 270°(8/16 bit)  
Fast, quiet, smooth and precise 2-Phase motors  
Smooth, fast and precise resolution for PAN/TILT movement with low noise operation  
Scan position memory, auto reposition after unexpected movement  
PAN/TILT reversible

## Built-in Programs

Different built-in dynamic effect with variable speed  
Different preset colors

## Color System

Face 1:  
RGB  
Smooth and pure color mixing capability  
CTO, 2800K-5600K color temperature adjustment  
Face 2:  
Warm white+cold white  
Smooth and pure color mixing capability  
CTO, 2500K-4600K color temperature adjustment

## Strobe Effect

0-25Hz LED shutter/strobe effect with variable speed

## Dimming System

0-100% Smooth linear LED dimming

## Control System

9/18 DMX channels USITT DMX-512 DMX512, master-slave, sound or auto operation  
DMX recorder and edit function integrated  
RDM available  
(Remote Device Management)  
Art-NET (Optional)  
Wireless receiver system built-in (Optional)  
Shielded input signal protection for stable signal without interference  
RJ45 etherCON IN/OUT (Optional with Art-Net)  
3-Pin and 5-pin  
XLR DMX connectors IN/OUT

## Software Update

Software up-datable through DMX connectors  
Mult units up-datable in daisy chain

## Display System

1.44" TFT LCD display  
5 Control buttons  
180°Reversible for LCD display  
Display auto OFF  
DMX signal and error monitoring indicators

## Cooling System

Advanced low noise self-adjusting fan cooling system integrated aluminum  
Constant temperature readout and management function  
Over temperature protection management

## Power Supply

Electronic supply with active PFC  
AC100-240V 50/60Hz  
PowerCON connectors IN&OUT  
340W Power consumption

## Housing

High tension molded fire proof housing with PA6+fibres  
Skeleton made of aluminum and steel metal plates  
Two side handles on base  
Exterior finish: Black

## Installation

2\*1/4 turn fastening Omega Clamps (Adaptable vertically and horizontally)  
1\*Safety attachment point

## Operating Condition

Operating positions: all (device on floor or fixed to a support)  
-25°C to 45°C ambient temperature  
IP20 protection rating

## Compliance

CE  
2014/35/EU - Safety of electrical equipment supplied at low voltage (LVD)  
2014/30/EU - Electromagnetic Compatibility (EMC)  
2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)

## Weight

N.W.: 7.23 kg  
G.W.: 9.16 kg

## Dimensions

Product Dimensions:  
139(D)\*297.9(W)\*376.7(H)mm  
Packing Dimensions:  
405(D)\*365(W)\*295(H)mm

