

SMARTPAR 715EP

Model:IP715E



The SMARTPAR 715EP is an IP65 rated high power outdoor LED flat par light with auxiliary effects using 7*15W 5-IN-1 RGBWA LEDs+60*0.2W 3-IN-1 RGB LEDs. It's available for 2800K-5600K color temperature adjustment.

It features excellent color mixing, quiet running and flicker free control. The fixture is built in with internal dynamic effects with variable speed. The PAR also features optimum optic design integrated with extremely effective aluminum heat sink system.

The SMARTPAR 715EP is designed for applications as concerts, TV studios, conference halls, bars, pubs, DJ entertainment, architectural lighting projects, gardens, theme parks, etc.



Light Source

Source: 7*15W 5-IN-1 LEDs (RGBWA)
60*0.2W 3-IN-1 LEDs (RGB)

Flicker free operation for broadcast TV and FILM

Life Span: 50000H

The life span may vary depending on several following factors but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming)

Optics

High efficiency optic system
25°Beam angle (other angles optional)
35°Field angle
High output

Color System

RGBWA for main light
Smooth and pure color mixing capability
CTO, 2800K-5600K color temperature adjustment
RGB for auxiliary light
Background colors adjustable for auxiliary light

Built-in Programs

Different built-in dynamic effect with variable speed
Different preset colors

Installation

1*Safety attachment point

Strobe Effect

0-25Hz LED shutter/strobe effect with variable speed

Dimming System

0-100% Smooth linear LED dimming

Control System

8/9/11/19/185 DMX channels USITT
DMX-512
DMX512, master-slave, sound or auto operation
DMX recorder and edit function integrated
IR Remote control
RDM available (Remote Device Management)
Wireless system as optional
Shielded input signal protection for stable signal without interference
IP65 Rated 3-pin XLR connectors IN/OUT

Display System

1.44" TFT LCD display
4 Touch control buttons
180°Reversible for LCD display
Display auto OFF
DMX signal and error monitoring indicators

Cooling System

Efficient noise free cooling system integrated aluminum
Constant temperature readout and management function
Over temperature protection management

Power Supply

Electronic supply with active PFC
AC100-240V 50/60Hz
IP65 Rated PowerCON connectors IN&OUT
126W Power consumption

Housing

Aluminum die-casting structure
2 Hanging brackets
Exterior finish: Black

Operating Condition

Operating positions:
all (device on floor or fixed to a support)
-25 C to 45 C ambient temperature
IP65 protection rating

Compliance

CE
2014/35/EU - Safety of electrical equipment supplied at low voltage (LVD)
2014/30/EU - Electromagnetic Compatibility (EMC)
2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)

Weight

N.W.: 5.06kg
G.W.: 5.91kg(1PCS)/25.57kg(4PCS)

Dimensions

Product Dimensions:
132.5(D)*280(W)*315.5(H)mm
Packing Dimensions:
360(D)*310(W)*200(H)mm (1PCS)
375(D)*655(W)*440(H)mm (4PCS)

