

SMARTSTROBE 3245

Model:MH3245



The NO-FAN designed SMARTSTROBE 3245 is an ultra compact and light weight stylish moving head wash/strobe light featuring 324*0.5W 5730 WW+CW LEDs which is designed with 9 individual rings. It's available for 2500K-4600K color temperature adjustment. The fixture could be used not just only as a wash light (specially moving face light) but also as a remarkable moving strobe light.

It provides 360° continuous fast and smooth PAN/TILT movement with variable speed which delivers even more vivid visual effect to the show. The fixture supports DMX, RDM (Remote Device Management).

It features excellent color mixing, quiet running and flicker free control. The fixture is built in with different internal dynamic effect with variable speed. The moving head also features optimum optic design integrated with extremely effective aluminum heat sink system.

The fixture's exterior housing is beautifully balanced basing on a modern design philosophy with supremely harmonious interior structure for remarkable control. The sculpted body of the SMARTSTROBE 3245 achieves more than just a striking look. The 2*1/4 turn fastening omega clamps, available for vertical and horizontal plug-in, make installations fast and easy.

The SMARTSTROBE 3245 is designed for applications as concerts, TV studios, banquet halls, bars, pubs, DJ entertainment, ballrooms, etc.

Light Source

Source:324*0.5W 5730 LEDs (WW+CW)
9 Individual control rings
Flicker free operation for broadcast TV and FILM
Life Span: 50000H
The life span may vary depending on several following factors but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming)

Optics

120°Field angle
High output

Movement

PAN: 2 modes
1. 360°Continuous movement
2. 540°(8/16 bit)
TILT: 2 modes
1. 360°Continuous movement
2. 270°(8/16 bit)
Fast, quiet, smooth and precise 2-Phase motors
Smooth, fast and precise resolution for PAN/TILT movement with low noise operation
Scan position memory, auto reposition after unexpected movement
PAN/TILT reversible

Color System

Warm white+cold white
Smooth and pure color mixing capability
CTO, 2500K-4600K color temperature adjustment

Built-in Programs

Different built-in dynamic effect with variable speed
Different preset colors

Strobe Effect

0-25Hz LED shutter/strobe effect with variable speed

Dimming System

0-100% Smooth linear LED dimming

Control System

3/4/5/8/9 DMX channels USITT DMX-512 DMX512, master-slave, sound or auto operation
DMX recorder and edit function integrated
RDM available (Remote Device Management)
Art-NET (Optional)
Wireless receiver system built-in (Optional)
Shielded input signal protection for stable signal without interference
RJ45 etherCON IN/OUT (Optional with Art-Net)
3-Pin and 5-pin XLR DMX connectors IN/OUT

Software Update

Software up-dateable through DMX connectors
Muilt units up-dateable in daisy chain

Display System

1.44" TFT LCD display
5 Control buttons
180°Reversible for LCD display
Display auto OFF
DMX signal and error monitoring indicators

Cooling System

Advanced noise-free cooling system integrated aluminum (NO-FAN)
Constant temperature readout and management function
Over temperature protection management

Power Supply

Electronic supply with active PFC
AC100-240V 50/60Hz
PowerCON connectors IN&OUT
190W Power consumption

Housing

High tension molded fire proof housing with PA6+fibre
Skeleton made of aluminum and steel metal plates
Two side handles on base
Exterior finish: Black

Installation

2*1/4 turn fastening Omega Clamps (Adaptable vertically and horizontally)
1*Safety attachment point

Operating Condition

Operating positions:
all (device on floor or fixed to a support)
-25 C to 45 C ambient temperature
IP20 protection rating

Compliance

CE
2014/35/EU - Safety of electrical equipment supplied at low voltage (LVD)
2014/30/EU - Electromagnetic Compatibility (EMC)
2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)

Weight

N.W.: 6.82 kg
G.W.: 8.7 kg

Dimensions

Product Dimensions:
139(D)*297.9(W)*376.7(H)mm
Packing Dimensions:
405(D)*365(W)*295(H)mm

